



EASISOLV 140

ON PRESS CLEANER

EasiSolv 140 On Press Cleaner is designed to remove all inks from the screen printing mesh. This product evaporates quickly and should not be rinsed with water. 140 is to be used during on press color changes, saved screens, removing ink from squeegees, floodbars and other equipment.

SPECIAL FEATURES:

- EasiSolv 140 effectively dissolves most inks, including: conventional/solvent, UV, plastisol and water base.
- EasiSolv 140 is non-flammable which makes it safer for handling, storage and rag disposal than conventional solvent cleaners.
- EasiSolv 140 dries fast providing a safe, odor-free alternative to hazardous, flammable solvents.
- EasiSolv 140 may be applied manually or recirculated through the EasiFlo™ System, or in an enclosed, automatic screen washing system, providing superior product life and economy.

APPLICATION FOR USE:

- Scrape all excess ink from screen.
- Apply EasiSolv 140 by squirt bottle, pneumatic sprayer or by rag to the ink side of the screen.
- Thoroughly agitate ink with a rag or scrubber, then wipe up all dissolved ink.
- Reapply if necessary and follow with a dry rag, wipe on both sides of the screen.
- The screen will be ready for printing or tape application within 20 seconds.

PHYSICAL AND CHEMICAL DATA:

Appearance & Odor:

Clear liquid with aromatic odor

Specific Gravity:

0.93 @ 20° C / 68° F

pH:

Neutral

VOC:

930 grams/liter

Flash Point:

61° C / 142° F

Ink Types:

Plastisol
UV
Conventional/Solvent
Water Base

Product Family:

Textile
Graphic