

**Safety Data Sheet**  
**7127 Performance Pro™ Gold**



SDS Revision Date:

10/28/2014

**1. Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Product Identity** 7127 Performance Pro™ Gold  
**Alternate Names** Plastisol Screen Printing Inks

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Intended use** Screen Printing.  
**Application Method** See Technical Data Sheet.

**1.3. Details of the supplier of the safety data sheet**

**Company Name** International Coatings Company, Inc.  
13929 East 166th Street  
Cerritos, CA 90702-7666

**Emergency**

**24 hour Emergency Telephone No.** (800) 255-3924  
**Customer Service: International Coatings Company, Inc.** (562) 926-1010

**2. Hazard identification of the product**

**2.1. Classification of the substance or mixture**

Acute Tox. 5;H313 May be harmful in contact with skin. (Not adopted by US OSHA)

**2.2. Label elements**

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.

**Warning**

H313 May be harmful in contact with skin.

**[Prevention]:**

P260 Do not breathe mist / vapors / spray.  
P262 Do not get in eyes, on skin, or on clothing.

**[Response]:**

P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician.  
P312 Call a POISON CENTER or doctor / physician if you feel unwell.  
P331 Do NOT induce vomiting.

**[Storage]:**

# Safety Data Sheet

## 7127 Performance Pro™ Gold



SDS Revision Date:

10/28/2014

No GHS storage statements

**[Disposal]:**

No GHS disposal statements

### 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Calcium carbonate CAS Number: 0001317-65-3	10 - 25		[1][2]
2,2,4-trimethylpentane-1,3-diyl dibenzoate CAS Number: Proprietary	10 - 25		[1]
Alkylsulfonic Acid Ester of Phenol CAS Number: Proprietary	10 - 25	Acute Tox. 4;H312	[1]
PVC (Chloroethylene, polymer) CAS Number: Proprietary	10 - 25		[1]
Titanium dioxide CAS Number: 0013463-67-7	1.0 - 10		[1][2]
Polyvinyl Chloride/Polyvinyl Acetate Copolymer CAS Number: Proprietary	1.0 - 10		[1]
Pigment yellow 83 CAS Number: 0005567-15-7	1.0 - 10		[1]
Epoxidised soya oil CAS Number: 0008013-07-8	1.0 - 10		[1]
Amorphous fumed silica CAS Number: 0112945-52-5	1.0 - 10		[1]
Pigment yellow 151 CAS Number: 0031837-42-0	1.0 - 10		[1]
Stoddard solvent CAS Number: 0008052-41-3	0.1 - 1.0	STOT RE 1;H372 Asp. Tox. 1;H304	[1][2]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the phrases are shown in Section 16.

### 4. First aid measures

#### 4.1. Description of first aid measures

**General**

In all cases of doubt, or when symptoms persist, seek medical attention.  
Never give anything by mouth to an unconscious person.

**Inhalation**

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate

# Safety Data Sheet

## 7127 Performance Pro™ Gold



SDS Revision Date:

10/28/2014

<b>Eyes</b>	medical attention. Give nothing by mouth. Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
<b>Skin</b>	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
<b>Ingestion</b>	If the person is conscious, induce vomiting immediately by giving 2 glasses of water and pressing finger down the throat. Repeat until vomit is clear, then give milk. Contact a physician immediately.

#### 4.2. Most important symptoms and effects, both acute and delayed

**Overview** Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

**Eyes** Causes serious eye irritation.

## 5. Fire-fighting measures

### 5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO<sub>2</sub>, powder, water spray.  
Do not use; water jet.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Hydrogen chloride (if heated), carbon monoxide and carbon dioxide.

Do not breathe mist / vapors / spray.

Do not get in eyes, on skin, or on clothing.

### 5.3. Advice for fire-fighters

In the event of fire, wear full protective clothing and NIOSH Approved Self-contained breathing apparatus with full face piece operated in the pressure demand or other positive pressure mode. Move container from fire area if it can be done without risk. Use water to keep fire exposed containers cool and disperse vapors.

**ERG Guide No.** ----

## 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

# Safety Data Sheet

## 7127 Performance Pro™ Gold



SDS Revision Date:

10/28/2014

Wear protective equipment as listed in Section 8 during clean up operations.

### 6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

### 6.3. Methods and material for containment and cleaning up

Ventilate the area and avoid breathing vapors. Take the personal protective measures listed in section 8.

Contain and absorb spillage with non-combustible materials e.g. sand, earth, vermiculite. Place in closed containers outside buildings and dispose of according to the Waste Regulations. (See section 13).

Clean, preferably with a detergent. Do not use solvents.

Do not allow spills to enter drains or watercourses.

If drains, sewers, streams or lakes are contaminated, inform the local water company immediately. In the case of contamination of rivers, streams or lakes the Environmental Protection Agency should also be informed.

## 7. Handling and storage

### 7.1. Precautions for safe handling

See section 2 for further details. - [Prevention]:

### 7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Store in cool dry place. Elevated temperatures thicken product and shorten useful life.

Incompatible materials: Composition: Avoid contact with strong acids, alkali or oxidizing agents.

See section 2 for further details. - [Storage]:

### 7.3. Specific end use(s)

No data available.

## 8. Exposure controls and personal protection

### 8.1. Control parameters

#### Exposure

CAS No.	Ingredient	Source	Value
0001317-65-3	Calcium carbonate	OSHA	TWA 15 mg/m3 (total) TWA 5 mg/m3 (resp)
		ACGIH	TWA: 10 mg/m3 Ceiling: 20 mg/m3
		NIOSH	TWA 10 mg/m3 (total) TWA 5 mg/m3 (resp)
		Supplier	No Established Limit

# Safety Data Sheet

## 7127 Performance Pro™ Gold



SDS Revision Date:

10/28/2014

0005567-15-7	Pigment yellow 83	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0008013-07-8	Epoxidised soya oil	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0008052-41-3	Stoddard solvent	OSHA	TWA 500 ppm (2900 mg/m3)
		ACGIH	TWA: 290 mg/m3 STEL: 580 mg/m3
		NIOSH	TWA 350 mg/m3 C 1800 mg/m3 [15-minute]
		Supplier	No Established Limit
0013463-67-7	Titanium dioxide	OSHA	TWA 15 mg/m3
		ACGIH	TWA: 10 mg/m3 2B, Revised 2006,
		NIOSH	Ca
		Supplier	No Established Limit
0031837-42-0	Pigment yellow 151	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0112945-52-5	Amorphous fumed silica	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
Proprietary	2,2,4-trimethylpentane-1,3-diyl dibenzoate	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
Proprietary	Alkylsulfonic Acid Ester of Phenol	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
Proprietary	Polyvinyl Chloride/Polyvinyl Acetate Copolymer	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
Proprietary	PVC (Chloroethylene, polymer)	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

# Safety Data Sheet

## 7127 Performance Pro™ Gold



SDS Revision Date:

10/28/2014

### Carcinogen Data

CAS No.	Ingredient	Source	Value
0001317-65-3	Calcium carbonate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0005567-15-7	Pigment yellow 83	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0008013-07-8	Epoxidised soya oil	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0008052-41-3	Stoddard solvent	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0013463-67-7	Titanium dioxide	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
0031837-42-0	Pigment yellow 151	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0112945-52-5	Amorphous fumed silica	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
Proprietary	2,2,4-trimethylpentane-1,3-diyl dibenzoate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
Proprietary	Alkylsulfonic Acid Ester of Phenol	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
Proprietary	Polyvinyl Chloride/Polyvinyl Acetate Copolymer	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
Proprietary	PVC (Chloroethylene, polymer)	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

## 8.2. Exposure controls

### Respiratory

Not Required

### Eyes

Wear safety eyewear, e.g. safety spectacles, goggles or visors to protect against the splash of liquids.

# Safety Data Sheet

## 7127 Performance Pro™ Gold



SDS Revision Date:

10/28/2014

- Skin** Neoprene gloves are recommended.
- Engineering Controls** Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.
- Other Work Practices** Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

### 9. Physical and chemical properties

<b>Appearance</b>	Smooth thick Liquid
<b>Odor</b>	Faint
<b>Odor threshold</b>	Not Measured
<b>pH</b>	Not Measured
<b>Melting point / freezing point</b>	Not Measured
<b>Initial boiling point and boiling range</b>	Not Measured
<b>Flash Point</b>	Not Measured
<b>Evaporation rate (Ether = 1)</b>	Not Measured
<b>Flammability (solid, gas)</b>	Not Applicable
<b>Upper/lower flammability or explosive limits</b>	<b>Lower Explosive Limit:</b> Not Measured <b>Upper Explosive Limit:</b> Not Measured
<b>Vapor pressure (Pa)</b>	Not Measured
<b>Vapor Density</b>	Not Measured
<b>Specific Gravity</b>	1.45-1.55
<b>Solubility in Water</b>	Not Measured
<b>Partition coefficient n-octanol/water (Log Kow)</b>	Not Measured
<b>Auto-ignition temperature</b>	Not Measured
<b>Decomposition temperature</b>	Not Measured
<b>Viscosity (cSt)</b>	Not Measured
<b>VOC %</b>	< 0.1 lb/gallon
<b>% Volatile</b>	< 1

#### 9.2. Other information

No other relevant information.

### 10. Stability and reactivity

#### 10.1. Reactivity

# Safety Data Sheet

## 7127 Performance Pro™ Gold



SDS Revision Date:

10/28/2014

Hazardous Polymerization will not occur.

### 10.2. Chemical stability

Stable under normal circumstances.

### 10.3. Possibility of hazardous reactions

No data available.

### 10.4. Conditions to avoid

Avoid exposure to heat and humidity.

### 10.5. Incompatible materials

Composition: Avoid contact with strong acids, alkali or oxidizing agents.

### 10.6. Hazardous decomposition products

Hydrogen chloride (if heated), carbon monoxide and carbon dioxide.

## 11. Toxicological information

### Acute toxicity

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
Calcium carbonate - (1317-65-3)	No data available	No data available	No data available	No data available	No data available
2,2,4-trimethylpentane-1,3-diyl dibenzoate - (Proprietary)	No data available	No data available	No data available	No data available	No data available
Alkylsulfonic Acid Ester of Phenol - (Proprietary)	> 5,000.00, Rat - Category: NA	> 1,000, Rat - Category: 4	No data available	No data available	No data available
Titanium dioxide - (13463-67-7)	10,000.00, Rat - Category: NA	10,000.00, Rabbit - Category: NA	No data available	6.82, Rat - Category: NA	No data available
PVC (Chloroethylene, polymer) - (Proprietary)	No data available	No data available	No data available	No data available	No data available
Polyvinyl Chloride/Polyvinyl Acetate Copolymer - (Proprietary)	No data available	No data available	No data available	No data available	No data available
Pigment yellow 83 - (5567-15-7)	5,000.00, Rat - Category: 5	No data available	No data available	No data available	No data available
Epoxidised soya oil - (8013-07-8)	21,000.00, Rat - Category: NA	2,000.00, Rabbit - Category: 4	No data available	No data available	No data available
Amorphous fumed silica - (112945-52-5)	3,160.00, Rat -	No data	No data	No data	No data



# Safety Data Sheet

## 7127 Performance Pro™ Gold



SDS Revision Date:

10/28/2014

	Category: 5	available	available	available	available
Pigment yellow 151 - (31837-42-0)	No data available	No data available	No data available	No data available	No data available
Stoddard solvent - (8052-41-3)	No data available	No data available	No data available	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	5	May be harmful in contact with skin. (Not adopted by US OSHA)
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

## 12. Ecological information

### 12.1. Toxicity

#### Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Calcium carbonate - (1317-65-3)	Not Available	Not Available	Not Available
2,2,4-trimethylpentane-1,3-diyl dibenzoate - (Proprietary)	Not Available	Not Available	Not Available
Alkylsulfonic Acid Ester of Phenol - (Proprietary)	Not Available	Not Available	Not Available
Titanium dioxide - (13463-67-7)	1,000.00, Fundulus heteroclitus	5.50, Daphnia magna	5.83 (72 hr), Pseudokirchneriella subcapitata

# Safety Data Sheet

## 7127 Performance Pro™ Gold



SDS Revision Date:

10/28/2014

PVC (Chloroethylene, polymer) - (Proprietary)	Not Available	Not Available	Not Available
Polyvinyl Chloride/Polyvinyl Acetate Copolymer - (Proprietary)	Not Available	Not Available	Not Available
Pigment yellow 83 - (5567-15-7)	18.00, Oncorhynchus mykiss	Not Available	Not Available
Epoxidised soya oil - (8013-07-8)	900.00, Leuciscus idus	100.00, Daphnia magna	8.00 (72 hr), Scenedesmus subspicatus
Amorphous fumed silica - (112945-52-5)	Not Available	Not Available	Not Available
Pigment yellow 151 - (31837-42-0)	Not Available	Not Available	Not Available
Stoddard solvent - (8052-41-3)	Not Available	Not Available	Not Available

### 12.2. Persistence and degradability

There is no data available on the preparation itself.

### 12.3. Bioaccumulative potential

Not Measured

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

### 12.6. Other adverse effects

No data available.

## 13. Disposal considerations

### 13.1. Waste treatment methods

Do not allow into drains or water courses. Wastes and emptied containers should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act.

Using information provided in this data sheet advice should be obtained from the Waste Regulation Authority, whether the special waste regulations apply.

## 14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
<b>14.1. UN number</b>	Not Applicable	Not Regulated	Not Regulated
<b>14.2. UN proper shipping name</b>	Not Regulated	Not Regulated	Not Regulated
<b>14.3. Transport hazard</b>	DOT Hazard Class: Not	IMDG: Not Applicable	Air Class: Not Applicable

# Safety Data Sheet

## 7127 Performance Pro™ Gold



SDS Revision Date:

10/28/2014

<b>class(es)</b>	Applicable <b>DOT Label:</b> ---	<b>Sub Class:</b> Not Applicable	
<b>14.4. Packing group</b>	Not Applicable	Not Applicable	Not Applicable
<b>14.5. Environmental hazards</b>			
<b>IMDG</b>	Marine Pollutant: Yes		
<b>14.6. Special precautions for user</b>			
No further information			

### 15. Regulatory information

**Regulatory Overview** The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

**Toxic Substance Control Act ( TSCA)** All components of this material are either listed or exempt from listing on the TSCA Inventory.

**WHMIS Classification** Not Regulated

**US EPA Tier II Hazards**

- Fire:** No
- Sudden Release of Pressure:** No
- Reactive:** No
- Immediate (Acute):** Yes
- Delayed (Chronic):** No

**EPCRA 311/312 Chemicals and RQs:**  
(No Product Ingredients Listed)

**EPCRA 302 Extremely Hazardous :**  
(No Product Ingredients Listed)

**EPCRA 313 Toxic Chemicals:**  
Butyl diglycol

**Proposition 65 - Carcinogens (>0.0%):**  
Crystalline Silica - Quartz

**Proposition 65 - Developmental Toxins (>0.0%):**  
(No Product Ingredients Listed)

**Proposition 65 - Female Repro Toxins (>0.0%):**  
(No Product Ingredients Listed)

**Proposition 65 - Male Repro Toxins (>0.0%):**  
(No Product Ingredients Listed)

**N.J. RTK Substances (>1%):**

- Chloroethylene, polymer
- Calcium carbonate
- Titanium dioxide

# Safety Data Sheet

## 7127 Performance Pro™ Gold

SDS Revision Date:

10/28/2014



### Penn RTK Substances (>1%):

Calcium carbonate

Titanium dioxide

## 16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H372 Causes damage to organs through prolonged or repeated exposure.

**This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.**

International Coatings Co., Inc. believes to the best of its knowledge that the information provided herein, is factual and the recommendations made are accurate as of the date shown. However, no representation or warranty is made as to their completeness or accuracy.

End of Document