

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

PRODUCT IDENTIFIER

Product CodeGLV-1030Product NameBRILLIANT REDProduct CategoryGLOSS VINYL SERIES SCREEN INK (GLV)

RECOMMENDED USE OF THE CHEMICAL AND RESTRICTIONS ON USE

Recommended Use PRINTING OPERATION

DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Inktech International Corporation

160 Fenmar Drive, Toronto, Ontario M9L 1M6 Tel: 1-416-743-4111 Fax: 1-416-743-1511

EMERGENCY TELEPHONE NUMBER

Chemtrec 1-613-996-6666

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION

Acute Toxicity - Inhalation	Category 4 - (H332)
Serious Eye Damage/ Irritation	Category 2 - (H319)
Specific Target Organ Toxicity (Single Exposure)	Category 3 - (H335)
Flammable Liquid	Category 3 - (H226)

LABEL ELEMENTS



SIGNAL WORD: DANGER!

HAZARD STATEMENTS

H332 Harmful if inhaled

- H319 Causes serious eye irritation
- H335 May cause respiratory irritation
- H226 Flammable liquid and vapor

PRECAUTIONARY STATEMENTS

- P331 Do not induce vomiting
- P210 Keep away from heat/ sparks/open flames/ hot surfaces No smoking.

HAZARDS NOT OTHERWISE CLASSIFIED (HNOC)

May be harmful in contact with skin.

SECTION 3. COMPOSITION/ INFORMATION ON INGREDIENTS

Mixture:

COMPONENTS	WEIGHT %	CAS NO	NOTE
ISOPHORONE	15-40	78-59-1	
PETROLEUM NAPHTHA, HEAVY AROMATIC	10-30	64742-94-5	
2-METHOXY-1-METHYL ETHYL ACETATE	7-13	108-65-6	
DIACETONE ALCOHOL	5-10	123-42-2	

SECTION 4. FIRST AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

General Advice

Show this safety data sheet to the doctor in attendance.

Eye Contact

Immediately flush with plenty of water. After flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops and persists.

Skin Contact

Wash immediately with soap and plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation such as redness, rash, blistering develops, get medical attention.

Inhalation

Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately.

Ingestion

Do Not induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control immediately.

MOST IMPORTANT SYMPTOMS AND EFECTS, BOTH ACCUTE AND DELAYED

None under normal use conditions.

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT

Notes to Physician: Treat symptomatically.

SECTION 5. FIRE FIGHTING PROCEDURE

SUITABLE EXTINGUISHING MEDIA

Foam, Carbon Dioxide (CO2), Dry chemical, and Water Spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

UNSUITABLE EXTINGUISHING MEDIA:

No information available.

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions.

PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIREFIGHTERS

As in any fire, wear self contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers/ tanks with water spray. Sealed containers may rupture when heated.

SECTION 6. ACCIDENTAL RELEASE MEASURE

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Personal Precautions

Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin, and clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people away from upwind of spill/leak.

Environmental Precautions

Prevent products from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches. Local authorities should be notified if significant spillages cannot be contained.

Methods and Material for Containment and Cleanup

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/ national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

SECTION 7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

Handling

Use personal protective equipment as required. Do not eat, drink, or smoke when using this product. Ensure adequate ventilation.

CONDITIONS FOR SAFE STORAGE INCLUDING ANY INCOMPATIBILITES

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep container closed when not in use. Keep out of reach of children.

Incompatible Products

Strong acids, strong bases, strong oxidizing and reducing agents.

SECTION 8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

CONTROL PARAMETERS

Exposure Limits

Component	ACGIH TLV	OSHA PEL	
Isophorone	Ceiling: 5 ppm	TWA: 4 ppm	
78-59-1		TWA: 23 mg/3	
		TWA: 25 ppm	
		TWA: 140 mg/m ³	
2-Methoxy-1-Methyl Ethyl Acetate	TWA: 50 ppm		
108-65-6			
Diacetone Alcohol	TWA: 50 ppm	TWA: 50 ppm	
123-42-2		TWA: 240 mg/m ³	

Component	Ontario TWAEV	Mexico OEL (TWA)
Isophorone	CEV: 5 ppm	TWA: Peak 5 ppm
78-59-1		TWA: Peak 25 mg/3
Diacetone Alcohol	TWA: 50 ppm	TWA/LMPE-PPT: 50 ppm
123-42-2	TWA: 240 mg/m ³	TWA/LMPE-PPT: 240 mg/m ³
	STEL: 75 ppm	STEL/LMPE-CT: 75 ppm
	STEL: 360 mg/m ³	STEL/LMPE-CT: 360 mg/m ³

APPROPRIATE ENGINEERING CONTROLS

Engineering Measures

Provide a good standard of general ventilation. Natural ventilation is from doors, windows, etc. Controlled ventilation means air is supplied or removed by powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In case of insufficient ventilation, wear suitable respiratory equipment.

INDIVIDUAL PROTECTION MEASURES SUCH AS PERSONAL PROTECTIVE EQUIPMENT

Eye /Face Protection:

Wear safety glasses with side shields (or goggle). If splashes are likely to occur, wear suitable face shield. Ensure the eye wash stations and safety showers are close to the workstation location.

Skin Protection:

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent contact.

Respiratory Protection:

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Wash hands before eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of equipment, work area and clothing is recommended.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State Odor	Viscous Liquid Sharp	Appearance Odor Threshold	Colored Liquid No information Available
Property PH Molting Point/Eroozing Point	<u>Values</u>	<u>Remarks/ Method</u> No Data Available No Data Available	
Melting Point/ Freezing Point Boiling Point/ Boiling Range	> 145 °C/ 293 °F 57.8 °C/ 136 °F		
Flash Point Evaporation Rate	57.8 C/136 F	Penskey Martens Close No Data Available	a Cup (PMCC)
Flammability Limit in Air Upper Flammability Limit (% vol)		No Data Available	
Lower Flammability Limit (% vol) Vapor Pressure		No Data Available No Data Available	
Vapor Density Specific Gravity	1.35	(Air=1) 4.3	
Water Solubility Solubility in Other Solvents		No Data Available No Data Available	
Partition Coefficient: N-Octanol/ Water Auto Ignition Temperature		No Data Available No Data Available	
Decomposition Temperature Kinetic Viscosity		No Data Available No Data Available	
Dynamic Viscosity		No Data Available	
Explosive Property Oxidizing Property		No Data Available No Data Available	

SECTION 10. STABILITY AND REACTIVITY

Reactivity

Chemical Stability

Conditions to Avoid

No information Available

Stable under normal condition

Possibility of Hazardous Reactions None under normal processing

Keep away from open flames, hot surfaces and sources of ignition

Incompatible Materials

Strong acids, strong bases, reducing agent.

Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating gases and vapors, Carbon Dioxide (CO2), Carbon Monoxide.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation	There is no data for this product
Eye Contact	There is no data for this product
Skin Contact	There is no data for this product
Ingestion	There is no data for this product

Component	CAS No.	Oral LD50
Isophorone	78-59-1	1500 mg/kg (Rat)
Petroleum Naphtha, Heavy Aromatic	64742-94-5	5000 mg/kg (Rat)
2-Methoxy -1 Methyl Ethyl Acetate	105-65-6	8532 mg/kg (Rat)
Diacetone Alcohol	123-42-2	4 g/kg (Rat)

Component	CAS No.	LD50 Dermal
Isophorone	78-59-1	1200 mg/kg (Rabbit)
Petroleum Naphtha, Heavy Aromatic	64742-94-5	>2000 mg/kg (Rabbit)
2-Methoxy -1 Methyl Ethyl Acetate	105-65-6	>19200 mg/kg (Rabbit)
Diacetone Icohol	123-42-2	13500 mg/kg (Rabbit)

Component	CAS No.	Inhalation LC50
Isophorone	78-59-1	7 mg/L (Rat) 4h
Petroleum Naphtha, Heavy Aromatic	64742-94-5	>590 mg/m3 (Rat) 4h
2-Methoxy -1 Methyl Ethyl Acetate	105-65-6	>5320 ppm (28.7 mg/L)(Rat) vapour

Information on Toxicological Effects

Symptoms	There is no data for this product.
Delayed and Immediate Effec	ts as well as Chronic Effects from Short and Long Term Exposure.
Skin Corrosion/ Irritation Eye Damage/ Irritation Irritation Corrositivity Sensitization Mutagenic Effects Reproductive Effects STOT – Single exposure STOT- Repeated Exposure Chronic Toxicity Aspiration Hazard	There is no data for this product. There is no data for this product. There is no data for this product There is no data for this product. There is no data for this product.
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.
-	

Component	CAS No.	ACGIH
Isophorone	78-59-1	A3

SECTION 12. ECOLOGICAL INFORMATION

Etoxicity

None known

0% of the mixture consists of components of unknown hazards to the aquatic environment.

Component	CAS No.	Algae/ Aquatic Plants
Isophorone	78-59-1	76 h EC50 Pseudokirchneriella Subcapitata: 51.1 – 342 mg/L
2-Methoxy -1 Methyl Ethyl Acetate	105-65-6	96 h EC50 >1000 mg/L or 72h (Green Algae)

Component	CAS No.	Fish
Isophorone	78-59-1	96 h LC50 Pimephales Promelas: 132-156 mg/L (flow through) 96 h LC50 Lepomis Macrochirus: 180-250 mg/L (static)
		96 h LC50 Pimephales Promelas: 213-271 mg/L (static)
2-Methoxy -1 Methyl Ethyl Acetate	105-65-6	96 h LC50 Flathead Minnow: 161 mg/L
Diacetone Alcohol	123-42-2	96 h LC50 Lepomis Macrochirus: 420 mg/L
		96 h LC50 Lepomis Macrochirus: 420 mg/L (static)

Component	CAS No.	Crustacea
Isophorone	78-59-1	48 h EC50 Daphnia Magna: 117 mg/L
2-Methoxy -1 Methyl Ethyl Acetate	105-65-6	48 h EC50 Daphnia Magna: 408 mg/L
Diacetone Alcohol	123-42-2	24 h EC50 Daphnia Magna: 8750 mg/L

Persistence and Degradability

No information Available

Bioaccumulation

No information Available

Component	CAS No.	Partition Coefficient
Petroleum Naphtha, Heavy aromatic	64742-94-5	4.5
Isophorone	78-59-1	1.66
Diacetone Alcohol	123-42-2	1.03

Other Adverse Effects: No information available.

SECTION 13. DISPOSAL CONSIDERATIONS

Waste Treatments Methods

Waste Disposal Methods Contain and dispose of waste according to local regulations.

Contaminated Packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT NFORMATION

DOT

In Canada and US, this material may be reclassified as a combustible liquid and is not regulated, via Surface transportation, in containers less than 119 gallons or 450 liters [per 49 CFR 173.150 (f)] [per Transportation of Dangerous Goods Regulations/ Clear Language Part 1.33]

UN/ ID No.	UN 1210
Proper Shipping name:	Printing Ink
Hazard Class:	3
Packing Group:	III

ICAO/ IATA/ IMDG/ IMO

UN/ ID No.	UN 1210
Proper Shipping name:	Printing Ink
Hazard Class:	3
Packing Group:	111

SECTION 15. REGULATORY INFORMATION

International Inventories

All components are listed on the TSCA Inventory. For further information, please contact: Supplier (manufacturer/importer/ downstream user/ distributor.

US Federal Regulations

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPS) (see 40 CFR 61)

This product contains the following substances which are listed hazardous pollutants (HAPS) under section 112 of the Clear Air Act.

Component	CAS NO.	Weight %
Isophorone	78-59-1	15-40

U.S. State Regulations

Component	CAS NO.	Massachusetts Right to Know
Isophorone	78-59-1	Х
Diacetone Alcohol	123-42-2	X

Component	CAS NO.	Minnesota Right to Know
Isophorone	78-59-1	х
Diacetone Alcohol	123-42-2	х

Component	CAS NO.	New Jersey Right to Know
Isophorone	78-59-1	X
Diacetone Alcohol	123-42-2	X
Component	CAS NO.	Pennsylvania Right to Know
Isophorone	78-59-1	X
Diacetone Alcohol	123-42-2	X

<u>Canada</u>

Component	NPRI – National Pollutant Release Inventory	
Isophorone	Part 4. Substance as set out in Section 65 of the List of Toxic Substance in	
78-59-1	Schedule 1 of the Canadian Environmental Protection Act 1999	
Petroleum Naphtha, Heavy Aromatic	Part 5. Other Groups and Mixtures. Part 4 Substances as set out in Section 65 of	
647-42-94-5	the List of Toxic Substance in Schedule 1 of the Canadian Environmental	
	Protection Act 1999	
Diacetone Alcohol	Part 4. Substance as set out in Section 65 of the List of Toxic Substance in	
123-42-2	Schedule 1 of the Canadian Environmental Protection Act 1999	

SECTION 16. OTHER INFORMATION

<u>HMIS</u>	Health 2*	Flammability 2	Reactivity 0	Personal Protection x
Key or lege	end to abbreviations and acronyr	<u>ms used in safety data sh</u>	leet.	
Legend – S TWA STEL Ceiling	Section 8: Exposure Controls/Per Time Weighted Average Short Term Average Maximum Limit Value	rsonal Protection		
ACGIH A1 A2 A3	American Conference of Goverr Known Human Carcinogen Suspended Human Carcinogen Animal Carcinogen		t	

IARC	International Agency for Research on Cancer
------	---

- Group 1 Carcinogenic to Humans
- Group 2A Probably Carcinogenic to Humans
- Group 2B Possibly Carcinogenic to Human

NTP National Toxicity Program

Known Known Carcinogen Reasonably Anticipated to be a Human Carcinogen

OSHA Occupational Health and Safety Administration

X Present

Date Nov. 24, 2016

DISCLAIMER

This information provided in this Safety Data sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of SDS