

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

PRODUCT IDENTIFIER

Product Code	GP-1540
Product Name	PEACOCK BLUE
Product Category	GENERAL PURPOSE SERIES SCREEN INK (GP)

RECOMMENDED USE OF THE CHEMICAL AND RESTRICTIONS ON USE

Recommended Use PRINTING OPERATION

DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Inktech International Corporation 160 Fenmar Drive, Toronto, Ontario M9L 1M6 Tel: 1-416-743-4111 Fax: 1-416-743-1511

EMERGENCY TELEPHONE NUMBER

Chemtrec 1-613-996-6666

SECTION 2. HAZARDS IDENTIFICATION

CLASSIFICATION

Acute Toxicity – Oral	Category 4 - (H302)
Acute Toxicity – Dermal	Category 4 - (H312)
Acute Toxicity - Inhalation	Category 4 - (H332)
Skin Irritation	Category 2 - (H315)
Serious Eye Damage/ Irritation	Category 2 - (H319)

LABEL ELEMENTS



SIGNAL WORD: DANGER!

HAZARD STATEMENTS

- H302 Harmful if swallowed
- H312 Harmful in contact with skin
- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H332 Harmful if inhaled

PRECAUTIONARY STATEMENTS

P331 – Do not induce vomiting

P210 – Keep away from heat/ sparks/open flames/ hot surfaces – No smoking.

HAZARDS NOT OTHERWISE CLASSIFIED (HNOC)

May be harmful in contact with skin.

SECTION 3. COMPOSITION/ INFORMATION ON INGREDIENTS

Mixture:

COMPONENTS	WEIGHT %	CAS NO	NOTE
DIACETONE ALCOHOL	30-60	123-42-2	
2-BUTOXYETHANOL	10-20	111-76-2	
PETROLEUM NAPHTHA, LIGHT AROMATIC	5-15	64742-95-6	
TITANIUM DIOXIDE	4-15	13463-67-7	
SILICON DIOXIDE	1-5	7631-86-9	
ALUMINUM HYDROXIDE	1-5	21645-512	

SECTION 4. FIRST AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

General Advice

Show this safety data sheet to the doctor in attendance.

Eye Contact

Immediately flush with plenty of water. After flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention if irritation develops and persists.

Skin Contact

Wash immediately with soap and plenty of water for at least 15 minutes. Remove contaminated clothing. If irritation such as redness, rash, blistering develops, get medical attention.

Inhalation

Remove person to fresh air and keep comfortable for breathing. If breathing is irregular or stopped, administer artificial respiration. Get medical attention immediately.

Ingestion

Do Not induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or poison control immediately.

MOST IMPORTANT SYMPTOMS AND EFECTS, BOTH ACCUTE AND DELAYED

None under normal use conditions.

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT

Notes to Physician: Treat symptomatically.

SECTION 5. FIRE FIGHTING PROCEDURE

SUITABLE EXTINGUISHING MEDIA

Foam, Carbon Dioxide (CO2), Dry chemical, and Water Spray. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

UNSUITABLE EXTINGUISHING MEDIA:

No information available.

SPECIFIC HAZARDS ARISING FROM THE CHEMICAL

Thermal decomposition can lead to release of irritating gases and vapors. May emit toxic fumes under fire conditions.

PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIREFIGHTERS

As in any fire, wear self contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool containers/ tanks with water spray. Sealed containers may rupture when heated.

SECTION 6. ACCIDENTAL RELEASE MEASURE

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

Personal Precautions

Remove all sources of ignition. Ventilate the area. Avoid contact with eyes, skin, and clothing. Avoid breathing dust or vapor. Evacuate personnel to safe areas. Keep people away from upwind of spill/leak.

Environmental Precautions

Prevent products from entering drains. Prevent further leakage or spillage if safe to do so. Keep out of drains, sewers, ditches. Local authorities should be notified if significant spillages cannot be contained.

Methods and Material for Containment and Cleanup

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local/ national regulations (see section 13). Use clean non-sparking tools to collect absorbed material.

SECTION 7. HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING

Handling

Use personal protective equipment as required. Do not eat, drink, or smoke when using this product. Ensure adequate ventilation.

CONDITIONS FOR SAFE STORAGE INCLUDING ANY INCOMPATIBILITES

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep container closed when not in use. Keep out of reach of children.

Incompatible Products

Strong acids, strong bases, strong oxidizing and reducing agents.

SECTION 8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

CONTROL PARAMETERS

Exposure Limits

Component	ACGIH TLV	OSHA PEL
Titanium Dioxide	TWA: 10 mg/m ³	TWA: 10 mg/m ³ (Total Dust)
13463-67-7		TWA: 15 mg/m ³ (Total Dust)
Silicon Dioxide		TWA: 6 mg/m ³
7631-86-9		
2-Butoxyethanol	TWA: 20 ppm	TWA: 25 ppm
111-76-2		TWA: 120mg/ ³
		TWA: 50 ppm
		TWA: 240 mg/m ³ Skin
Diacetone Alcohol	TWA: 50 ppm	TWA: 50 ppm
123-42-2		TWA: 240 mg/m ³

Component	Ontario TWAEV	Mexico OEL (TWA)
Titanium Dioxide	TWA: 10 mg/m ³ (total dust)	TWA/LMPE-PPT: 10 mg/m ³ (as TI)
13463-67-7		STEL/LMPE-CT: 20 mg/m ³ (as TI)
		TWA/LMPE-PPT: 26 ppm
2-Butoxyethanol	TWA: 20 ppm	TWA/LMPE-PPT: 120 mg/m ³
111-76-2		STEL/LMPE-CT: 75 ppm
		STEL/LMPE-CT: 360 mg/m ³
Diacetone Alcohol	TWA: 50 ppm	TWA/LMPE-PPT: 50 ppm
123-42-2	TWA: 240 mg/m ³	TWA/LMPE-PPT: 240 mg/m ³
	STEL: 75 ppm	STEL/LMPE-CT: 75 ppm
	STEL: 360 mg/m ³	STEL/LMPE-CT: 360 mg/m ³

APPROPRIATE ENGINEERING CONTROLS

Engineering Measures

Provide a good standard of general ventilation. Natural ventilation is from doors, windows, etc. Controlled ventilation means air is supplied or removed by powered fan. Users are advised to consider national Occupational Exposure Limits or other equivalent values. In case of insufficient ventilation, wear suitable respiratory equipment.

INDIVIDUAL PROTECTION MEASURES SUCH AS PERSONAL PROTECTIVE EQUIPMENT

Eye /Face Protection:

Wear safety glasses with side shields (or goggle). If splashes are likely to occur, wear suitable face shield. Ensure the eye wash stations and safety showers are close to the workstation location.

Skin Protection:

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent contact.

Respiratory Protection:

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Wash hands before eating, drinking or smoking. Wash contaminated clothing before reuse. Avoid contact with eyes, skin and clothing. Wear suitable gloves and eye/face protection. Regular cleaning of equipment, work area and clothing is recommended.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State Odor	Viscous Liquid Mild	Appearance Odor Threshold	Colored Liquid No information Available
Property	<u>Values</u>	Remarks/ Method	
PH Malifia Data (East and Data (No Data Available	
Melting Point/ Freezing Point		No Data Available	
Boiling Point/ Boiling Range	> 145 °C/ 293 °F		
Flash Point	52 °C/ 126 °F	Penskey Martens Closed Cup (PMC	C)
Evaporation Rate		No Data Available	
Flammability Limit in Air			
Upper Flammability Limit (% vol)		No Data Available	
Lower Flammability Limit (% vol)		No Data Available	
Vapor Pressure		No Data Available	
Vapor Density		Heavier than air	
Specific Gravity	0.98-1.3		
Water Solubility		No Data Available	
Solubility in Other Solvents		No Data Available	
Partition Coefficient: N-Octanol/ Water		No Data Available	
Auto Ignition Temperature		No Data Available	
Decomposition Temperature		No Data Available	
Kinetic Viscosity		No Data Available	
Dynamic Viscosity		No Data Available	
Explosive Property		No Data Available	
Oxidizing Property		No Data Available	

SECTION 10. STABILITY AND REACTIVITY

Reactivity

No information Available

Chemical Stability

Stable under normal condition

Possibility of Hazardous Reactions None under normal processing

Conditions to Avoid Keep away from open flames, hot surfaces and sources of ignition

Incompatible Materials

Strong acids, strong bases, reducing agent.

Hazardous Decomposition Products

Thermal decomposition can lead to release of irritating gases and vapors, Carbon Dioxide (CO2), Carbon Monoxide.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation	There is no data for this product
Eye Contact	There is no data for this product
Skin Contact	There is no data for this product
Ingestion	There is no data for this product

Component	CAS No.	Oral LD50
Petroleum Naphtha, Light Aromatic	64742-95-6	8400 mg/kg (Rat)
Diacetone Alcohol	123-42-2	4000 mg/kg (Rat)
2-Butoxyethanol	111-76-2	470 mg/kg (Rat)
Titanium Dioxide	13463-67-7	>10000 mg/kg (Rat)
Aluminum Hydroxide	108-94-1	800 mg/kg (Rat)
Silicon Dioxide	7631-869	>5000 mg/kg (Rat)

Component	CAS No.	LD50 Dermal
Petroleum Naphtha, Light Aromatic	64742-95-6	>2000 mg/kg (Rabbit)
Diacetone Alcohol	123-42-2	13500 mg/kg (Rabbit)
2-Butoxyethanol	111-76-2	220 mg/kg (Rabbit)
		2270 mg/kg (Rat)
Silicon Dioxide	7631-869	>2000 mg/kg (Rabbit)
	1001000	

Component	CAS No.	Inhalation LC50
Petroleum Naphtha, Light Aromatic	64742-95-6	3400 ppm (Rat) 4h
		>5.2 mg/L (Rat) 4h
2-Butoxyethanol	111-76-2	2.21 mg/L (Rat) 4h
		450 ppm (Rat) 4h
Diacetone Alcohol	123-42-2	7.23 gg/m³ (Rat) 4h
Silicon Dioxide	7631-869	>2.2 mg/L (Rat)

Information on Toxicological Effects

Symptoms

There is no data for this product.

Delayed and Immediate Effects as well as Chronic Effects from Short and Long Term Exposure.

Skin Corrosion/ Irritation	There is no data for this product.
Eye Damage/ Irritation	There is no data for this product.
Irritation	There is no data for this product
Corrositivity	There is no data for this product.
Sensitization	There is no data for this product.
Mutagenic Effects	There is no data for this product.
Reproductive Effects	There is no data for this product.
STOT – Single exposure	There is no data for this product.
STOT- Repeated Exposure	There is no data for this product.
Chronic Toxicity	There is no data for this product.
Aspiration Hazard	There is no data for this product.
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS No.	IARC	
Titanium Dioxide	13463-67-7	Group 2B	
Component	CAS No.	ACGIH	
2-Butoxyethanol	111-76-2	A3	
Component	CAS No.	OSHA	
Titanium Dioxide	13463-67-7	Х	

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

None known

0% of the mixture consists of components of unknown hazards to the aquatic environment.

Component	CAS No.	Algae /Aquatic Plants	
Silicon Dioxide	7631-86-9	72 h EC50 Pseudokirchneriella Subcapitata:440 mg/L	
2-Butoxyethanol	111-76-2	72 h EC50 Pseudokirchneriella Subcapitata:911 mg/L	
Component	CAS No.	Fish	
Petroleum Naphtha, light aromatic	64741-95-6	96 h LC50 Oncorhynchus Mykiss: 9.22 mg/L	
2-Butoxyethanol	xyethanol 111-76-2 96 h LC50 Lepomis Macrochirus: 14		
-		96 h LC50 Lepomis Macrochirus: 2950mg/L	
Diacetone Alcohol	123-42-2	96 h LC50 Lepomis Macrochirus: 420 mg/L	
		96 h LC50 Lepomis Macrochirus: 420 mg/L (Static)	
Silicon Dioxide	7631-86-9	96 h LC50 Brachydario Rerio: 5000 mg mg/L (Static)	

Component	CAS No.	Crustacea
Diacetone Alcohol	123-42-2	24 h EC50 Daphnia Magna: 8750 mg/L
2-Butoxyethanol	111-76-2	24 h EC50 Daphnia Magna: 1698-1940 mg/L
		48 h EC50 Daphnia Magna: >1000 mg/L
Silicon Dioxide	7631-86-9	48 h EC50 Cerioddaphnia Dubia: 7600mg/L

Persistence and Degradability

No information Available

Bioaccumulation

No information Available

Component	CAS No.	Partition Coefficient
Diacetone Alcohol	123-42-2	1.03
2-Butoxyethanol	111-76-2	0.81

Other Adverse Effects: No information available

SECTION 13. DISPOSAL CONSIDERATIONS

Waste Treatments Methods

Waste Disposal Methods Contain and dispose of waste according to local regulations.

Contaminated Packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

DOT

In Canada and US, this material may be reclassified as a combustible liquid and is not regulated, via Surface transportation, in containers less than 119 gallons or 450 liters [per 49 CFR 173.150 (f)] [per Transportation of Dangerous Goods Regulations/ Clear Language Part 1.33]

UN/ ID No.	UN 1210
Proper Shipping name:	Printing Ink
Hazard Class:	3
Packing Group:	111

ICAO/ IATA/ IMDG/ IMO

UN/ ID No. UN 1210 Proper Shipping name: Printing Ink Hazard Class: 3

SECTION 15. REGULATORY INFORMATION

International Inventories

All components are listed on the TSCA Inventory. For further information, please contact: Supplier (manufacturer/importer/ downstream user/ distributor.

US Federal Regulations

<u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Component	CAS NO.	Weight %	SARA 313 Threshold Values
2 Butoxyethanol	111-76-2	10-30	1.0

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPS) (see 40 CFR 61)

This product does not contain air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

U.S. State Regulations

Component	CAS NO.	Massachusetts Right to Know
Titanium Dioxide	13463-67-7	X
2-Butoxyethanol	111-76-2	X
Diacetone Alcohol	123-42-2	X
Silicon Dioxide	7631-86-9	Х

Component	CAS NO.	Minnesota Right to Know
Titanium Dioxide	13463-67-7	X
2-Butoxyethanol	111-76-2	X
Diacetone Alcohol	123-42-2	X
Silicon Dioxide	7631-86-9	X

Component	CAS NO.	New Jersey Right to Know
Titanium Dioxide	13463-67-7	х
2-Butoxyethanol	111-76-2	x
Diacetone Alcohol	123-42-2	x
Silicon Dioxide	7631-86-9	X

Component	CAS NO.	Pennsylvania Right to Know
Titanium dioxide	13463-67-7	X
2-Butoxyethanol	111-76-2	X
Diacetone Alcohol	123-42-2	X
Silicon Dioxide	7631-86-9	X

California Prop. 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

Component	California Prop. 65
Titanium Dioxide	Carcinogen

<u>Canada</u>

Component	NPRI – National Pollutant Release Inventory
Petroleum Naphtha, Light Aromatic	Part 5. Other Groups and Mixtures
64742-95-6	
Diacetone Alcohol	Part 4. Substances as set out in Section 65 of the List of Toxic Substances in
123-42-2	Schedule 1 of the Canadian Environmental Protection Act 1999
2 Butoxyethanol	Part 1. Group A substance, Part 5 Individual Substance, Part 4, Substances as

111-76-2		set out in Section 65 of the L	ist of Toxic Substance in Sc	bedule 1 of the
Canadian Environmental Pro				
GP-1540 PEA	ACOCK BLUE	•		Jan. 31, 2019
		SECTION 16. OTHER	INFORMATION	
HMIS	Health	Flammability	Reactivity	Personal Protection
	2*	2	0	x
Key or lege	end to abbreviations and ac	ronyms used in safety data	sheet.	
Legend – S TWA STEL Ceiling	ection 8: Exposure Contro Time Weighted Average Short Term Average Maximum Limit Value	Is/Personal Protection		
ACGIH A1 A2 A3	American Conference of Governmental Industrial Hygienist Known Human Carcinogen Suspended Human Carcinogen Animal Carcinogen			
IARC I Group 1 Group 2A Group 2B	nternational Agency for Re Carcinogenic to Humans Probably Carcinogenic to H Possibly Carcinogenic to H	Humans		
NTP Known Reasonably	National Toxicity Program Known Carcinogen Anticipated to be a Humar	n Carcinogen		
OSHA X	Occupational Health and Second	Safety Administration		
Date	Jan. 31, 2019			

DISCLAIMER

This information provided in this Safety Data sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of SDS