

Article No.: 22056 ESTELAN 700 Blue
Print date 05.12.2015 Revision date 26.06.2015 EN
Version 2.0 Issue date 12.05.2015 Page 1 / 7

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifiers

Article No. (manufacturer/supplier): 22056
Identification of the substance or mixture ESTELAN 700 Blue

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Lacquer. Reserved for industrial and professional use.

1.3. Details of the supplier of the safety data sheet

supplier (manufacturer/importer/downstream user/distributor)

KISSEL + WOLF GmbH
In den Ziegelwiesen 6 Telephone: 49 6222 578-0
69168 Wiesloch Telefax: 49 6222 578-100
E-mail: info@kiwo.de

Dept. responsible for information:

EHS Environment-Health-Safety
E-mail ehs@kiwo.de

1.4. Emergency telephone number

Emergency telephone number +49 6222 578 219

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

Flam. Liq. 3 / H226 flammable liquids Flammable liquid and vapour.

2.2. Label elements

The product is classified and labelled according to EC directives or corresponding national laws.

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Warning

Hazard statements

H226 Flammable liquid and vapour.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P370 + P378 In case of fire: Use Extinguishing powder or sand to extinguish.

P403 + P235 Store in a well-ventilated place. Keep cool.

contains:

n.a.

Supplemental Hazard information (EU)

n.a.

2.3. Other hazards

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Product description / chemical characterization

Description Mixture of components, as listed below, with nonhazardous constituents

Hazardous ingredients

Classification according to Regulation (EC) No. 1272/2008 [CLP]

EC No.	REACH No.	Wt %
CAS No.	Chemical name	Remark
INDEX No.	classification:	

Article No.: 22056 ESTELAN 700 Blue
Print date 05.12.2015 Revision date 26.06.2015
Version 2.0 Issue date 12.05.2015

EN
Page 2 / 7

203-603-9	01-2119475791-29	
108-65-6	2-methoxy-1-methylethyl acetate	35 - 50
607-195-00-7	Flam. Liq. 3 H226	
204-658-1	01-2119485493-29	
123-86-4	n-butyl acetate	5 - 7
607-025-00-1	Flam. Liq. 3 H226 / STOT SE 3 H336	
274-724-2		
70657-70-4	2-methoxypropyl acetate	0,1 - 0,15
607-251-00-0	Flam. Liq. 3 H226 / Repr. 1B H360 / STOT SE 3 H335	

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

After contact with skin, wash immediately with plenty of water and soap. Remove contaminated, saturated clothing immediately.

After eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

After ingestion

Seek medical advice immediately. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide Water mist Foam

Extinguishing media which must not be used for safety reasons:

strong water jet

5.2. Special hazards arising from the substance or mixture

Gases/vapours, toxic

5.3. Special protective equipment for firefighters:

Provide a conveniently located respiratory protective device.

Additional information

The danger areas must be delimited and identified using relevant warning and safety signs. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways. Treat runoff as hazardous.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Remove persons to safety. Do not breathe vapours. See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations. Provide good ventilation.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see chapter 13).

Article No.: 22056 ESTELAN 700 Blue
Print date 05.12.2015 Revision date 26.06.2015
Version 2.0 Issue date 12.05.2015

EN
Page 3 / 7

6.4. Reference to other sections

Observe protective provisions (see chapter 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Product may become electrostatically charged. When transferring, earthed pipework shall be used exclusively. Anti-static clothing including shoes are recommended. Use only spark proof tools. Avoid contact with skin and eyes. Do not inhale vapours or mist.

Do not eat, drink or smoke when using this product.

Personal protection equipment: refer to chapter 8.

Follow the legal protection and safety regulations.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep container tightly closed in a cool, well-ventilated place.

Requirements for storage rooms and vessels

Always keep in containers that correspond to the material of the original container. Ensure adequate ventilation of the storage area.

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Additional information

VCI-storage class, see Chapter 15

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

n-butyl acetate

INDEX No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4

TRGS 900, AGW, TWA: 300 mg/m³; 62 ppm

TRGS 900, AGW, STEL: 600 mg/m³; 124 ppm

2-methoxy-1-methylethyl acetate

INDEX No. 607-195-00-7 / EC No. 203-603-9 / CAS No. 108-65-6

TRGS 900, AGW, TWA: 270 mg/m³; 50 ppm

TRGS 900, AGW, STEL: 270 mg/m³; 50 ppm

2-methoxypropyl acetate

INDEX No. 607-251-00-0 / EC No. 274-724-2 / CAS No. 70657-70-4

TRGS 900, AGW, TWA: 28 mg/m³; 5 ppm

TRGS 900, AGW, STEL: 224 mg/m³; 40 ppm

Additional information

TWA : long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

DNEL:

n-butyl acetate

INDEX No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4

DNEL acute inhalative (local), Workers: 960 mg/m³

DNEL acute inhalative (systemic), Workers: 960 mg/m³

DNEL long-term inhalative (local), Workers: 480 mg/m³

DNEL long-term inhalative (systemic), Workers: 480 mg/m³

2-methoxy-1-methylethyl acetate

INDEX No. 607-195-00-7 / EC No. 203-603-9 / CAS No. 108-65-6

DNEL long-term dermal (systemic), Workers:

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 22056 ESTELAN 700 Blue
Print date 05.12.2015 Revision date 26.06.2015
Version 2.0 Issue date 12.05.2015

EN
Page 4 / 7

DNEL long-term inhalative (systemic), Workers: 275 mg/m³

PNEC:

n-butyl acetate

INDEX No. 607-025-00-1 / EC No. 204-658-1 / CAS No. 123-86-4

PNEC aquatic, freshwater: 0,18 mg/L

PNEC aquatic, marine water: 0,018 mg/L

PNEC aquatic, intermittent release: 0,36 mg/L

PNEC sediment, freshwater: 0,981 mg/kg

PNEC sediment, marine water: 0,0981 mg/kg

PNEC, Soil: 0,0903 mg/kg

PNEC sewage treatment plant (STP): 35,6 mg/L

2-methoxy-1-methylethyl acetate

INDEX No. 607-195-00-7 / EC No. 203-603-9 / CAS No. 108-65-6

PNEC aquatic, freshwater: 0,635 mg/L

PNEC aquatic, marine water: 0,0635 mg/L

PNEC sediment, freshwater: 3,29 mg/kg

PNEC sediment, marine water: 0,329 mg/kg

PNEC, Soil: 0,29 mg/kg

PNEC sewage treatment plant (STP): 100 mg/L

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

Hand protection

Chemical resistant protective gloves: DIN EN 374

Recommendation for contact by spatter: Protection Index 2

Permeation time >30 min., e.g. butyl rubber 0,4 mm

Recommendation for direct contact: Protection Index 6

Permeation time >480 min., e.g. nitrile rubber 0,4 mm

Eye protection

Wear closed protection glasses. DIN EN 166

Protective clothing

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:

Physical state

liquid

Colour

depending on coloration

Odour

typical

Safety relevant basis data

Flash point:

35 °C

Method

DIN 53213

Remark

Ignition temperature in °C

315 °C

Lower explosion limit

1,2 Vol-%

Upper explosion limit

12,7 Vol-%

Vapour pressure at 20 °C:

2,99 mbar

Density at 20 °C:

1,14 g/cm³

Water solubility (g/L)

partially soluble

pH at 20 °C:

-

Article No.: 22056 ESTELAN 700 Blue
Print date 05.12.2015 Revision date 26.06.2015
Version 2.0 Issue date 12.05.2015

EN
Page 5 / 7

Viscosity at 20 °C: 82 s 6 mm EN ISO 2431
Initial boiling point and boiling range 100 °C (101,3 kPa)
Decomposition temperature (°C): 0

9.2. **Other information:**

SECTION 10: Stability and reactivity

10.1. **Reactivity**

10.2. **Chemical stability**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.

10.3. **Possibility of hazardous reactions**

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. **Conditions to avoid**

10.5. **Incompatible materials**

10.6. **Hazardous decomposition products**

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

Classification for mixtures and used evaluation method according to regulation (EC) 1207/2008 [CLP]
No data on preparation itself available.

11.1. **Information on toxicological effects**

Acute toxicity

2-methoxy-1-methylethyl acetate
oral, LD50, Rat: > 5000 mg/kg
dermal, LD50, Rat: > 2000 mg/kg
dermal, LD50, Rabbit: > 0 mg/kg

skin corrosion/irritation; Serious eye damage/eye irritation

Toxicological data are not available.

Respiratory or skin sensitisation

Toxicological data are not available.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Toxicological data are not available.

Specific target organ toxicity

Toxicological data are not available.

Aspiration hazard

Toxicological data are not available.

Practical experience/human evidence

Other observations:

Prolonged or repeated contact with the preparation can lead to irritations of mucous membranes and of skin such as redness, formation of blebs, dermatitis, etc..In case of inhalation dizziness, Nausea Inhalation causes narcotic effects/intoxication.Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

EC No.	Chemical name
274-724-2	2-methoxypropyl acetate
70657-70-4	

Classification according to Regulation (EC) No. 1272/2008 [CLP]
Repr. 1B

Remark

There is no information available on the preparation itself .

Article No.: 22056 ESTELAN 700 Blue
Print date 05.12.2015 Revision date 26.06.2015
Version 2.0 Issue date 12.05.2015

EN
Page 6 / 7

SECTION 12: Ecological information

overall evaluation

Classification for mixtures and used evaluation method according to regulation (EC) 1207/2008 [CLP]
Do not store at public landfills.

12.1. Toxicity

2-methoxy-1-methylethyl acetate

Fish toxicity, LC50, Oncorhynchus mykiss: 134 mg/L (96 h)

Daphnia toxicity, EC50, Daphnia magna (Big water flea): > 500 mg/L (48 h)

Long-term Ecotoxicity

Toxicological data are not available.

12.2. Persistence and degradability

Toxicological data are not available.

12.3. Bioaccumulative potential

Toxicological data are not available.

Bioconcentration factor (BCF)

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

List of proposed waste codes/waste designations in accordance with EWC

080111 waste paint and varnish containing organic solvents or other dangerous substances

packaging

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

14.1. UN number

1263

14.2. UN proper shipping name

Land transport (ADR/RID):

Paint

Sea transport (IMDG):

PAINT

Air transport (ICAO-TI / IATA-DGR):

Paint

14.3. Transport hazard class(es)

Land transport (ADR/RID):

Not a class 3 product
Container > 450 l : class 3

Sea transport (IMDG)

3

for packages < 30 litres:

Transport in accordance with 2.3.2.5 of the IMDG Code.

Air transport (ICAO-TI / IATA-DGR)

3

14.4. Packing group

III

14.5. Environmental hazards

Land transport (ADR/RID)

n.a.

Marine pollutant

n.a.

14.6. Special precautions for user

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 22056 ESTELAN 700 Blue
Print date 05.12.2015 Revision date 26.06.2015
Version 2.0 Issue date 12.05.2015

EN
Page 7 / 7

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Additional information

Land transport (ADR/RID)

tunnel restriction code D/E

Sea transport (IMDG)

EmS-No. F-E, S-E

Packaging >30 l

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

VOC

VOC-value (in g/L): ISO 11890-2 581,635

VOC-value (in g/L): ASTM D 2369 590,022

Observe in addition any national regulations!

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

calculated with mixing rule

Substance/product listed in the following inventories:

Listed in TOXIC SUBSTANCES CONTROL ACT (TSCA)

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this preparation were not carried out.

SECTION 16: Other information

Full text of classification in section 3:

Flam. Liq. 3 / H226	flammable liquids	Flammable liquid and vapour.
STOT SE 3 / H336	Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness.
Repr. 1B / H360	Reproductive toxicity	May damage the unborn child.
STOT SE 3 / H335	Specific target organ toxicity (single exposure)	May cause respiratory irritation.

Additional information

Classification for mixtures and used evaluation method according to regulation (EC) 1207/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.