

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 25756
Print date 14.05.2015
Version 2.0

KIWOSOLV L 74
Revision date 12.05.2015
Issue date 12.05.2015

EN
Page 1 / 7

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifiers

Article No. (manufacturer/supplier): 25756
Identification of the substance or mixture KIWOSOLV L 74

1.2. Relevant identified uses of the substance or mixture and uses advised against
Relevant identified uses

Cleaner / Thinner. Reserved for industrial and professional use.

1.3. Details of the supplier of the safety data sheet

supplier (manufacturer/importer/downstream user/distributor)

KISSEL + WOLF GmbH
In den Ziegelwiesen 6
69168 Wiesloch

Telephone: 49 6222 578-0
Telefax: 49 6222 578-100
E-mail: info@kiwo.de

Dept. responsible for information:

EHS Environment-Health-Safety
E-mail

ehs@kiwo.de

1.4. Emergency telephone number

Emergency telephone number +49 6222 578 219

2. Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

Flam. Liq. 3 / H226 flammable liquids Flammable liquid and vapour.

2.2. Label elements

The product is classified and labelled according to EC directives or corresponding national laws.

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Warning

Hazard statements

H226 Flammable liquid and vapour.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P370 + P378 In case of fire: Use Extinguishing powder or sand to extinguish.
P403 + P235 Store in a well-ventilated place. Keep cool.

contains:

n.a.

Supplemental Hazard information (EU)

n.a.

2.3. Other hazards

3. Composition / Information on ingredients

3.2. Mixtures

Product description / chemical characterization

Description Mixture of components, as listed below, with nonhazardous constituents

Hazardous ingredients

Classification according to Regulation (EC) No. 1272/2008 [CLP]

EC No. REACH No.
CAS No. Chemical name
INDEX No. classification:

Wt %
Remark

Article No.: 25756 KIWOSOLV L 74
Print date 14.05.2015 Revision date 12.05.2015
Version 2.0 Issue date 12.05.2015

EN
Page 2 / 7

203-603-9	01-2119475791-29	
108-65-6	2-methoxy-1-methylethyl acetate	70 - 100
607-195-00-7	Flam. Liq. 3 H226	
274-724-2		
70657-70-4	2-methoxypropyl acetate	0,25 - 0,3
607-251-00-0	Flam. Liq. 3 H226 / Repr. 1B H360 / STOT SE 3 H335	

Additional information

Full text of classification: see section 16

4. First-aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

After contact with skin, wash immediately with plenty of water and soap. Remove contaminated, saturated clothing immediately.

After eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

After ingestion

Seek medical advice immediately. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide Water mist Foam

Extinguishing media which must not be used for safety reasons:

strong water jet

5.2. Special hazards arising from the substance or mixture

Gases/vapours, toxic

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device.

Additional information

The danger areas must be delimited and identified using relevant warning and safety signs. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways. Treat runoff as hazardous.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Remove persons to safety. Do not breathe vapours. See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations. Provide good ventilation.

6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see chapter 13).

6.4. Reference to other sections

Observe protective provisions (see chapter 7 and 8).

Article No.: 25756 KIWOSOLV L 74
Print date 14.05.2015 Revision date 12.05.2015
Version 2.0 Issue date 12.05.2015

EN
Page 3 / 7

7. Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Product may become electrostatically charged. When transferring, earthed pipework shall be used exclusively. Anti-static clothing including shoes are recommended. Use only spark proof tools. Avoid contact with skin and eyes. Do not inhale vapours or mist.

Do not eat, drink or smoke when using this product.

Personal protection equipment: refer to chapter 8.

Follow the legal protection and safety regulations.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep container tightly closed in a cool, well-ventilated place.

Requirements for storage rooms and vessels

Always keep in containers that correspond to the material of the original container. Ensure adequate ventilation of the storage area.

Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

Additional information

VCI-storage class, see Chapter 15

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

8. Exposure controls / Personal protection

8.1. Control parameters

Occupational exposure limit values:

2-methoxy-1-methylethyl acetate

INDEX No. 607-195-00-7 / EC No. 203-603-9 / CAS No. 108-65-6

TRGS 900, AGW, TWA: 270 mg/m³; 50 ppm

TRGS 900, AGW, STEL: 270 mg/m³; 50 ppm

2-methoxypropyl acetate

INDEX No. 607-251-00-0 / EC No. 274-724-2 / CAS No. 70657-70-4

TRGS 900, AGW, TWA: 28 mg/m³; 5 ppm

TRGS 900, AGW, STEL: 224 mg/m³; 40 ppm

Additional information

TWA : long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

DNEL:

2-methoxy-1-methylethyl acetate

INDEX No. 607-195-00-7 / EC No. 203-603-9 / CAS No. 108-65-6

DNEL long-term dermal (systemic), Workers:

DNEL long-term inhalative (systemic), Workers: 275 mg/m³

PNEC:

2-methoxy-1-methylethyl acetate

INDEX No. 607-195-00-7 / EC No. 203-603-9 / CAS No. 108-65-6

PNEC aquatic, freshwater: 0,635 mg/L

PNEC aquatic, marine water: 0,0635 mg/L

PNEC sediment, freshwater: 3,29 mg/kg

PNEC sediment, marine water: 0,329 mg/kg

PNEC, Soil: 0,29 mg/kg

PNEC sewage treatment plant (STP): 100 mg/L

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and

Article No.: 25756
Print date 14.05.2015
Version 2.0

KIWOSOLV L 74
Revision date 12.05.2015
Issue date 12.05.2015

EN
Page 4 / 7

solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

Personal protection equipment

Respiratory protection

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

Hand protection

Chemical resistant protective gloves: DIN EN 374
Recommendation for contact by spatter: Protection Index 2
Permeation time >30 min., e.g. butyl rubber 0,4 mm
Recommendation for direct contact: Protection Index 6
Permeation time >480 min., e.g. nitrile rubber 0,4 mm

Eye protection

Wear closed protection glasses. DIN EN 166

Protective clothing

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

This solvent is to be sent to recycling or to disposal after use. Incorrect disposal endangers the environment. After use, all mixtures with other foreign substances or solvents of other types is forbidden.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:

Physical state liquid
Colour depending on coloration
Odour typical

Safety relevant basis data

		Method	Remark
Flash point:	50 °C	DIN 53213	
Ignition temperature in °C	315 °C		
Lower explosion limit	1,5 Vol-%		
Upper explosion limit	10,8 Vol-%		
Vapour pressure at 20 °C:	4,99 mbar		
Density at 20 °C:	0,97 g/cm ³		
Water solubility (g/L)	insoluble		
pH at 20 °C:	-		
Viscosity at 23 °C:	11 s 4 mm	DIN 53211	
Initial boiling point and boiling range	140 °C (101,3 kPa)		
Decomposition temperature (°C):	0		

9.2. Other information:

10. Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.

10.3. Possibility of hazardous reactions

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. Conditions to avoid

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

11. Toxicological information

Article No.: 25756
Print date 14.05.2015
Version 2.0

KIWOSOLV L 74
Revision date 12.05.2015
Issue date 12.05.2015

EN
Page 5 / 7

Classification for mixtures and used evaluation method according to regulation (EC) 1207/2008 [CLP]
No data on preparation itself available.

11.1. Information on toxicological effects

Acute toxicity

2-methoxy-1-methylethyl acetate
oral, LD50, Rat: > 5000 mg/kg
dermal, LD50, Rat: > 2000 mg/kg
dermal, LD50, Rabbit: > 0 mg/kg

skin corrosion/irritation; Serious eye damage/eye irritation

Toxicological data are not available.

Respiratory or skin sensitisation

Toxicological data are not available.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Toxicological data are not available.

Specific target organ toxicity

Toxicological data are not available.

Aspiration hazard

Toxicological data are not available.

Practical experience/human evidence

Other observations:

Prolonged or repeated contact with the preparation can lead to irritations of mucous membranes and of skin such as redness, formation of blebs, dermatitis, etc..In case of inhalation dizziness, Nausea Inhalation causes narcotic effects/intoxication.Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

Overall Assessment on CMR properties

EC No. CAS No.	Chemical name	Classification according to Regulation (EC) No. 1272/2008 [CLP]
274-724-2 70657-70-4	2-methoxypropyl acetate	Repr. 1B

Remark

There is no information available on the preparation itself .

12. Ecological information

overall evaluation

Classification for mixtures and used evaluation method according to regulation (EC) 1207/2008 [CLP]
Do not store at public landfills.

12.1. Toxicity

2-methoxy-1-methylethyl acetate
Fish toxicity, LC50, Oncorhynchus mykiss: 134 mg/L (96 h)
Daphnia toxicity, EC50, Daphnia magna (Big water flea): > 500 mg/L (48 h)

Long-term Ecotoxicity

Toxicological data are not available.

12.2. Persistence and degradability

Toxicological data are not available.

12.3. Bioaccumulative potential

Toxicological data are not available.

Bioconcentration factor (BCF)

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

Article No.: 25756
Print date 14.05.2015
Version 2.0

KIWOSOLV L 74
Revision date 12.05.2015
Issue date 12.05.2015

EN
Page 6 / 7

12.5. Results of PBT assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

13. Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product Recommendation

List of proposed waste codes/waste designations in accordance with EWC

070704 other organic solvents, washing liquids and mother liquors

packaging

Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

14. Transport information

14.1. UN number

3272

14.2. UN proper shipping name

Land transport (ADR/RID):

Esters, n.o.s.
(Methoxypropyl acetate)

Sea transport (IMDG):

ESTERS, N.O.S.
(Methoxypropyl acetate)

Air transport (ICAO-TI / IATA-DGR):

Esters, n.o.s.
(Methoxypropyl acetate)

14.3. Transport hazard class(es)

3

14.4. Packing group

III

14.5. Environmental hazards

Land transport (ADR/RID)

n.a.

Marine pollutant

n.a.

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Additional information

Land transport (ADR/RID)

tunnel restriction code

D/E

Sea transport (IMDG)

EmS-No.

F-E, S-D

Packaging >30 l

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

not applicable

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

VOC

VOC-value (in g/L): ISO 11890-2

957,130

VOC-value (in g/L): ASTM D 2369

957,130

Observe in addition any national regulations!

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)
according to Regulation (EU) No 453/2010



Article No.: 25756 KIWOSOLV L 74
Print date 14.05.2015 Revision date 12.05.2015
Version 2.0 Issue date 12.05.2015

EN
Page 7 / 7

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).
calculated with mixing rule

Substance/product listed in the following inventories:

Listed in TOXIC SUBSTANCES CONTROL ACT (TSCA)

15.2. **Chemical Safety Assessment**

Chemical safety assessments for substances in this preparation were not carried out.

16. **Other information**

Full text of classification in section 3:

Flam. Liq. 3 / H226	flammable liquids	Flammable liquid and vapour.
Repr. 1B / H360	Reproductive toxicity	May damage the unborn child.
STOT SE 3 / H335	Specific target organ toxicity (single exposure)	May cause respiratory irritation.

Additional information

Classification for mixtures and used evaluation method according to regulation (EC) 1207/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.