

# SAFETY DATA SHEET

#### 1. Identification

Product number SW382

Product identifier **FAST TACK 382 PREMIUM MIST PALLET ADHESIVE** 

Company information Sprayway, Inc.

Company phone Emergency telephone US Emergency

1005 SOUTH WESTGATE DR ADDISON, IL 60101 United States

telephone outside

1-952-852-4646

US

Version #

Not available. Recommended use Recommended restrictions None known.

## 2. Hazard(s) identification

Physical hazards Flammable aerosols Category 1 Health hazards Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2A

Specific target organ toxicity, single exposure

Category 3 narcotic effects

Aspiration hazard

Category 1 Category 1

Environmental hazards Hazardous to the aquatic environment, acute

hazard

Hazardous to the aquatic environment,

long-term hazard

Category 1

OSHA defined hazards

Not classified.

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation.

Causes serious eye irritation. May cause drowsiness or dizziness.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open

flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area.

Wear protective gloves. Wear eye/face protection.

If swallowed: Immediately call a poison center/doctor. If on skin: Wash with plenty of water. If Response

inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. Specific treatment (see this label). Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from Storage

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations. Disposal

Hazard(s) not otherwise

classified (HNOC)

None known.

Product name: 13 OZ SW FAST TACK 382 MIST ADH LT 12PK Product #: 1000010130 Version #: 01 Issue date: 08-14-2014

36.25% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 36.25% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

## 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Acetone		67-64-1	20 - 40
n-Heptane		142-82-5	20 - 40
Butane		106-97-8	10 - 20
Propane		74-98-6	10 - 20
Pentane		109-66-0	2.5 - 10
Other components below reportable levels			10 - 20

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

Composition comments

For the full text of the R phrases mentioned in this Section, see Section 16.

### 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Take off immediately all contaminated clothing. Rinse skin with water/shower. Get medical Skin contact

attention if irritation develops and persists. Wash clothing separately before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Call a physician or poison control center immediately. Rinse mouth, Do not induce vomiting, If

vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

Aspiration may cause pulmonary edema and pneumonitis. Skin irritation. Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

Provide general supportive measures and treat symptomatically.

Take off all contaminated clothing immediately. Wash contaminated clothing before reuse. Ensure General information that medical personnel are aware of the material(s) involved, and take precautions to protect

themselves.

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Ingestion

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Fire-fighting equipment/instructions

General fire hazards

Water fog. Dry chemical powder. Alcohol resistant foam. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.

Extremely flammable aerosol.

### Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid discharge into drains, water courses or onto the ground. Environmental manager must be informed of all major releases.

Product name: 13 OZ SW FAST TACK 382 MIST ADH LT 12PK Product #: 1000010130 Version #: 01 Issue date: 08-14-2014

## 7. Handling and storage

Precautions for safe handling

Do not handle or store near an open flame, heat or other sources of ignition. All equipment used when handling the product must be grounded. Use non-sparking tools and explosion-proof equipment. Do not spray on a naked flame or any other incandescent material. Use only in

well-ventilated areas. Provide adequate ventilation. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with skin, eyes and clothing. Pressurized

container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not re-use empty containers. Wear appropriate personal protective equipment. Observe good

industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Keep away from heat, sparks and open flame. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

Occupational exposure limits

1000	
n-Heptane (CAS 142-82-5) Pentane (CAS 109-66-0) Pentane (CAS 109-66-0) Propane (CAS 74-98-6) PEL  1000 Propane (CAS 74-98-6) PEL  1000 US. ACGIH Threshold Limit Values Components Type Value Acetone (CAS 67-64-1) TWA  1000 Butane (CAS 106-97-8) STEL TWA 1000 N-Heptane (CAS 142-82-5) STEL TWA 1000 US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Acetone (CAS 67-64-1) TWA 1000 US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Acetone (CAS 106-97-8) TWA 1900 Retaine (CAS 106-97-8) TWA 1900 T	mg/m3
Pentane (CAS 109-66-0) PEL 2950 1000 Propane (CAS 74-98-6) PEL 1800 US. ACGIH Threshold Limit Values Components Type Value Acetone (CAS 67-64-1) STEL 750 p TWA 500 p Butane (CAS 106-97-8) STEL 1000 n-Heptane (CAS 142-82-5) STEL 500 p TWA 400 p Pentane (CAS 109-66-0) TWA 1000 US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Acetone (CAS 67-64-1) TWA 590 m 250 p Pentane (CAS 106-97-8) TWA 1900 Retrone (CAS 106-97-8) TWA 1900 Pentane (CAS 109-66-0) TWA 1900 TWA 1900 TWA 1900 TWA 1900 Pentane (CAS 109-66-0) TWA 1900 TWA 1900 TWA 1900 Pentane (CAS 142-82-5) Ceiling 1800 TWA 350 m 120 p TWA 120 p	ppm
Pentane (CAS 109-66-0)         PEL         2950           Propane (CAS 74-98-6)         PEL         1800           US. ACGIH Threshold Limit Values         1000           Components         Type         Value           Acetone (CAS 67-64-1)         STEL         750 p           TWA         500 p         5TEL         1000           n-Heptane (CAS 106-97-8)         STEL         1000         1000           n-Heptane (CAS 142-82-5)         TWA         1000         1000           US. NIOSH: Pocket Guide to Chemical Hazards         Components         Value           Acetone (CAS 67-64-1)         TWA         590 m           Butane (CAS 106-97-8)         TWA         1900 p           n-Heptane (CAS 106-97-8)         TWA         1900 p           n-Heptane (CAS 109-66-0)         Ceiling         1800 p           TWA         350 m         85 pp           Pentane (CAS 109-66-0)         Ceiling         1800           Fropane (CAS 74-98-6)         TWA         350 m           TWA         350 m         120 p           Propane (CAS 74-98-6)         TWA         1800           OH         1000         1000	mg/m3
1000	pm
Propane (CAS 74-98-6)         PEL         1800 1000           US. ACGIH Threshold Limit Values         Type         Value           Components         Type         Value           Acetone (CAS 67-64-1)         STEL         750 p           TWA         500 p         1000 p           n-Heptane (CAS 106-97-8)         STEL         1000 p           n-Heptane (CAS 142-82-5)         STEL         500 p           TWA         400 p         1000 p           US. NIOSH: Pocket Guide to Chemical Hazards         Components         Type           Acetone (CAS 67-64-1)         TWA         590 m           Acetone (CAS 106-97-8)         TWA         1900 p           n-Heptane (CAS 142-82-5)         Ceiling         1800 p           n-Heptane (CAS 142-82-5)         Ceiling         1800 p           TWA         350 m         85 pp           Pentane (CAS 109-66-0)         Ceiling         1800 p           TWA         350 m         120 p           Propane (CAS 74-98-6)         TWA         1800 p           Ogical limit values         ACGIH Biological Exposure Indices	mg/m3
US. ACGIH Threshold Limit Values Components  Type  Value  Acetone (CAS 67-64-1)  STEL  TWA  500 p  TWA  500 p  Butane (CAS 106-97-8)  n-Heptane (CAS 142-82-5)  TWA  400 p  Pentane (CAS 109-66-0)  US. NIOSH: Pocket Guide to Chemical Hazards Components  Type  Value  Acetone (CAS 67-64-1)  TWA  590 n  Acetone (CAS 106-97-8)  TWA  1900  n-Heptane (CAS 142-82-5)  Ceiling  TWA  1900  TWA  1900  TWA  1900  TWA  1900  TWA  1900  1000  Pentane (CAS 109-66-0)  TWA  1900  TWA  1900  TWA  1900  TWA  1900  1000  TWA  1000  1000  Ogical limit values  ACGIH Biological Exposure Indices	ppm
US. ACGIH Threshold Limit Values Components  Type  Value  Acetone (CAS 67-64-1)  STEL  TWA  500 p  TWA  500 p  Butane (CAS 106-97-8)  n-Heptane (CAS 142-82-5)  TWA  400 p  Pentane (CAS 109-66-0)  US. NIOSH: Pocket Guide to Chemical Hazards Components  Type  Value  Acetone (CAS 67-64-1)  TWA  590 m  Acetone (CAS 169-7-8)  TWA  1900  Butane (CAS 106-97-8)  TWA  1900  n-Heptane (CAS 142-82-5)  Ceiling  TWA  350 m  TWA  360 m  TWA  160 m	mg/m3
Components         Type         Value           Acetone (CAS 67-64-1)         STEL         750 p           TWA         500 p           Butane (CAS 106-97-8)         STEL         1000           n-Heptane (CAS 142-82-5)         STEL         500 p           TWA         400 p         1000           US. NIOSH: Pocket Guide to Chemical Hazards         Components         Type         Value           Acetone (CAS 67-64-1)         TWA         590 m         250 p           Butane (CAS 106-97-8)         TWA         1900 p         1900 p           n-Heptane (CAS 142-82-5)         Ceiling         1800 p         1800 p           TWA         350 m         440 p         1800 p           TWA         350 m         120 p         1800 p           Propane (CAS 74-98-6)         TWA         1800 p         1800 p           Ogical limit values         ACGIH Biological Exposure Indices         ACGIH Biological Exposure Indices	ppm
Acetone (CAS 67-64-1)  Acetone (CAS 106-97-8)  Butane (CAS 106-97-8)  NTWA  STEL  TWA  S00 p  STEL  1000  N-Heptane (CAS 142-82-5)  TWA  Pentane (CAS 109-66-0)  US. NIOSH: Pocket Guide to Chemical Hazards  Components  Type  Value  Acetone (CAS 67-64-1)  Butane (CAS 106-97-8)  TWA  1900  N-Heptane (CAS 142-82-5)  Ceiling  TWA  S50 p  Pentane (CAS 142-82-5)  Ceiling  TWA  S50 p  TWA  S61 p  TWA  S50 p	
TWA 500 p Butane (CAS 106-97-8) STEL 1000 n-Heptane (CAS 142-82-5) STEL 500 p Pentane (CAS 109-66-0) TWA 400 p Pentane (CAS 109-66-0) TWA 1000 US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Acetone (CAS 67-64-1) TWA 590 m 250 p Butane (CAS 106-97-8) TWA 1900 n-Heptane (CAS 142-82-5) Ceiling 1800 p Pentane (CAS 142-82-5) Ceiling 1800 p TWA 350 m 85 pp Pentane (CAS 109-66-0) Ceiling 1800 p TWA 350 m 87 p Propane (CAS 74-98-6) TWA 1800 p Propane (CAS 74-98-6) TWA 1800 p Ogical limit values ACGIH Biological Exposure Indices	
Butane (CAS 106-97-8) STEL 1000 n-Heptane (CAS 142-82-5) STEL 500 p TWA 400 p Pentane (CAS 109-66-0) TWA 1000 US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Acetone (CAS 67-64-1) TWA 590 m 250 p Butane (CAS 106-97-8) TWA 1900 n-Heptane (CAS 142-82-5) Ceiling 1800 n-Heptane (CAS 142-82-5) Ceiling 1800 Fentane (CAS 109-66-0) Ceiling 1800 Find TWA 350 m TWA	om
n-Heptane (CAS 142-82-5)	
TWA 400 p Pentane (CAS 109-66-0) TWA 1000  US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value  Acetone (CAS 67-64-1) TWA 590 m 250 p Butane (CAS 106-97-8) TWA 1900 n-Heptane (CAS 142-82-5) Ceiling 1800  TWA 350 m Fentane (CAS 109-66-0) Ceiling 1800  TWA 350 m 120 p Propane (CAS 74-98-6) TWA 1800 ogical limit values ACGIH Biological Exposure Indices	ppm
Pentane (CAS 109-66-0)  US. NIOSH: Pocket Guide to Chemical Hazards Components  Type  Value  Acetone (CAS 67-64-1)  Butane (CAS 106-97-8)  TWA  1900  n-Heptane (CAS 142-82-5)  Ceiling  TWA  350 m  85 pp  Pentane (CAS 109-66-0)  Ceiling  TWA  350 m  87 pp  TWA  TWA  TWA  TWA  TWA  TWA  TWA  T	pm
US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value  Acetone (CAS 67-64-1) TWA 590 m  250 p  Butane (CAS 106-97-8) TWA 1900 n-Heptane (CAS 142-82-5) Ceiling 1800 440 p  TWA 350 m  85 pp  Pentane (CAS 109-66-0) Ceiling 1800 610 p  TWA 350 m  Propane (CAS 74-98-6) TWA 1800 ogical limit values  ACGIH Biological Exposure Indices	
Components         Type         Value           Acetone (CAS 67-64-1)         TWA         590 m           Butane (CAS 106-97-8)         TWA         1900           n-Heptane (CAS 142-82-5)         Ceiling         1800           TWA         350 m           Pentane (CAS 109-66-0)         Ceiling         1800           TWA         350 m           120 p           Propane (CAS 74-98-6)         TWA         1800           Ogical limit values         ACGIH Biological Exposure Indices	opm
Acetone (CAS 67-64-1)  Acetone (CAS 67-64-1)  Butane (CAS 106-97-8)  TWA  1900 800 p n-Heptane (CAS 142-82-5)  Ceiling  TWA  350 m 85 pp Pentane (CAS 109-66-0)  Ceiling  TWA  350 m 120 p Propane (CAS 74-98-6)  TWA  1800 Ogical limit values ACGIH Biological Exposure Indices	
250 p Butane (CAS 106-97-8)   TWA   1900   800 p   n-Heptane (CAS 142-82-5)   Ceiling   1800   440 p   TWA   350 m   85 pp   Pentane (CAS 109-66-0)   Ceiling   1800   610 p   TWA   350 m   120 p   Propane (CAS 74-98-6)   TWA   1800   1000   ogical limit values   ACGIH Biological Exposure Indices	
Butane (CAS 106-97-8)  TWA  1900 800 p n-Heptane (CAS 142-82-5)  Ceiling  TWA  350 m 85 pp Pentane (CAS 109-66-0)  Ceiling  TWA  350 m 120 p Propane (CAS 74-98-6)  TWA  1800 1000  Ogical limit values  ACGIH Biological Exposure Indices	ıg/m3
n-Heptane (CAS 142-82-5)  Ceiling  TWA  350 m  85 pp  Pentane (CAS 109-66-0)  Ceiling  TWA  350 m  610 p  TWA  350 m  120 p  Propane (CAS 74-98-6)  TWA  1800  Ogical limit values  ACGIH Biological Exposure Indices	pm
n-Heptane (CAS 142-82-5)  Ceiling  TWA  350 m 85 pp Pentane (CAS 109-66-0)  Ceiling  TWA  350 m 85 pp TWA  350 m 120 p TWA  350 m 120 p Propane (CAS 74-98-6)  TWA  1800 1000  Ogical limit values  ACGIH Biological Exposure Indices	mg/m3
440 p TWA 350 m 85 pp Pentane (CAS 109-66-0) Ceiling 1800 610 p TWA 350 m 120 p Propane (CAS 74-98-6) TWA 1800 1000 ogical limit values ACGIH Biological Exposure Indices	pm
TWA 350 m 85 pp Pentane (CAS 109-66-0) Ceiling 1800 610 p TWA 350 m 120 p Propane (CAS 74-98-6) TWA 1800 00jical limit values ACGIH Biological Exposure Indices	mg/m3
Pentane (CAS 109-66-0)  Ceiling  TWA  TWA  350 m 120 p Propane (CAS 74-98-6)  TWA  1800  1000  Ogical limit values  ACGIH Biological Exposure Indices	pm
Pentane (CAS 109-66-0)  Ceiling  1800 610 p 610 p 7WA 350 m 120 p Propane (CAS 74-98-6)  TWA 1800 000 000 000 000 000 000 000 000 00	ıg/m3
TWA 350 m 120 p Propane (CAS 74-98-6) TWA 1800 1000 ogical limit values ACGIH Biological Exposure Indices	m
TWA 350 m 120 p Propane (CAS 74-98-6) TWA 1800 1000 ogical limit values ACGIH Biological Exposure Indices	mg/m3
Propane (CAS 74-98-6)  TWA  1800 1000  ogical limit values  ACGIH Biological Exposure Indices	pm
Propane (CAS 74-98-6) TWA 1800 1000 ogical limit values ACGIH Biological Exposure Indices	ıg/m3
ogical limit values ACGIH Biological Exposure Indices	-
ogical limit values ACGIH Biological Exposure Indices	mg/m3
ACGIH Biological Exposure Indices	ppm
	Sampling Time
Acetone (CAS 67-64-1) 50 mg/l Acetone Urine	*

Appropriate engineering

Explosion-proof general and local exhaust ventilation. Provide eyewash station.

controls

<sup>\* -</sup> For sampling details, please see the source document.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Hand protection Wear protective gloves.

Skin protection

considerations

Other Wear appropriate chemical resistant clothing.

If engineering controls do not maintain airborne concentrations below recommended exposure Respiratory protection

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

When using do not smoke. Always observe good personal hygiene measures, such as washing General hygiene

after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

Compressed liquefied gas. **Appearance** 

Physical state Gas.

Form Aerosol. Compressed gas.

Color Tan Solvent. Odor Odor threshold Not available.

Not applicable estimated рΗ

Melting point/freezing point Initial boiling point and boiling Not available. Not available.

range

-156.0 °F (-104.4 °C) Propellant estimated Flash point

Not available. Evaporation rate Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits Not available. Explosive limit - lower (%) Explosive limit - upper (%) Not available.

35 - 45 psig @ 70F estimated Vapor pressure

Vapor density Not available. Not available. Relative density

Solubility(ies)

Not available. Solubility (water) Not available. Auto-ignition temperature Not available. Decomposition temperature Not available. Viscosity

Other information

Specific gravity 0.686 estimated

### 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. Chemical stability Possibility of hazardous Hazardous polymerization does not occur.

reactions

Avoid heat, sparks, open flames and other ignition sources. Contact with incompatible materials. Conditions to avoid

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

No hazardous decomposition products are known.

products

## 11. Toxicological information

Information on likely routes of exposure

Smallest quantities reaching the lungs through swallowing or subsequent vomiting may result in Ingestion

lung edema or pneumonia.

Inhalation No adverse effects due to inhalation are expected.

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics If aspirated into lungs during swallowing or vomiting, may cause chemical pneumonia, pulmonary injury or death. Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause central nervous system effects. Symptoms

of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Information on toxicological effects

Expected to be a low hazard for usual industrial or commercial handling by trained personnel. Acute toxicity

Product	Species	Test Results
13 OZ SW FAST TACK 382	MIST ADH LT 12PK (CAS Mixture)	
Acute		
Dermal		
LD50	Rat	6723 mg/kg
Inhalation	_	
LC50	Rat	299 mg/l/4h
Oral	5 .	
LD50	Rat	
Components	Species	Test Results
Acetone (CAS 67-64-1)		
Acute		
Dermal LD50	Guinea pig	> 7426 mg/kg, 24 Hours
LD30	Guillea pig	
	D 113	> 9.4 ml/kg, 24 Hours
	Rabbit	> 7426 mg/kg, 24 Hours
		> 9.4 ml/kg, 24 Hours
Inhalation		
LC50	Rat	55700 ppm, 3 Hours
		132 mg/l, 3 Hours
		50.1 mg/l
Oral		
LD50	Rat	5800 mg/kg
		2.2 ml/kg
Butane (CAS 106-97-8)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
n-Heptane (CAS 142-82-5)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
Inhalation	_	
LC50	Rat	> 29.29 mg/l, 4 Hours

Product name: 13 OZ SW FAST TACK 382 MIST ADH LT 12PK Product #: 1000010130 Version #: 01 Issue date: 08-14-2014 Components **Species** Test Results Pentane (CAS 109-66-0) Acute Inhalation LC50 Rat > 25.3 mg/l, 4 Hours Propane (CAS 74-98-6) Acute Inhalation LC50 Mouse 1237 mg/l, 120 Minutes 52 %, 120 Minutes 1355 mg/l Rat 658 mg/l/4h Causes skin irritation. Skin corrosion/irritation Causes serious eye irritation. Serious eye damage/eye irritation Respiratory or skin sensitization Respiratory sensitization Not a respiratory sensitizer. Skin sensitization This product is not expected to cause skin sensitization. No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity mutagenic or genotoxic. Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050) Not listed. This product is not expected to cause reproductive or developmental effects. Reproductive toxicity Specific target organ toxicity -Narcotic effects. single exposure Specific target organ toxicity -Not classified. repeated exposure Aspiration hazard May be fatal if swallowed and enters airways. 12. Ecological information **Ecotoxicity** Very toxic to aquatic life with long lasting effects.

Product		Species	Test Results
13 OZ SW FAST TACK 382	MIST ADH LT 12	PK (CAS Mixture)	
Aquatic			
Crustacea	EC50	Daphnia	56000 mg/L, 48 Hours
Fish	LC50	Fish	118 mg/L, 96 Hours
Components		Species	Test Results
Acetone (CAS 67-64-1)			
Aquatic			
Crustacea	EC50	Daphnia	13999 mg/L, 48 Hours
		Water flea (Daphnia magna)	21.6 - 23.9 mg/l, 48 hours
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	4740 - 6330 mg/l, 96 hours
n-Heptane (CAS 142-82-5)			
Aquatic			
Fish	LC50	Mozambique tilapia (Tilapia mossambica)	375 mg/l, 96 hours
Pentane (CAS 109-66-0)			
Aquatic			
Crustacea	EC50	Daphnia	9.74 mg/L, 48 Hours
sistence and degradability	No data is ava	ailable on the degradability of this product.	

Product name: 13 OZ SW FAST TACK 382 MIST ADH LT 12PK

Product #: 1000010130 Version #: 01 Issue date: 08-14-2014

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

Acetone -0.24Butane 2.89 n-Heptane 4.66 Pentane 3.39 2.36 Propane

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

Dispose in accordance with all applicable regulations. Local disposal regulations

The waste code should be assigned in discussion between the user, the producer and the waste Hazardous waste code

disposal company.

US RCRA Hazardous Waste U List: Reference

Acetone (CAS 67-64-1) U002

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied.

## 14. Transport information

DOT

UN1950 UN number UN proper shipping name Aerosols

Transport hazard class(es)

Class 2.1 Subsidiary risk 2.1 Label(s)

Packing group Not applicable.

Special precautions for user Read safety instructions. SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Special provisions 153, N82 Packaging exceptions 306 Packaging non bulk None None Packaging bulk

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

IATA

**UN number** UN1950

UN proper shipping name

Transport hazard class(es)

Aerosols, flammable

Class 2.1 Subsidiary risk Label(s) Packing 2.1

group Environmental Not applicable.

hazards ERG Code Yes

10L

Read safety instructions, SDS and emergency procedures before handling. Read safety Special precautions for user

instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed.

Allowed. Cargo aircraft only LTD QTY **Packaging Exceptions** 

#### **IMDG**

UN1950 **UN** number UN proper shipping name **AEROSOLS** 

Transport hazard class(es)

2.1 Class Subsidiary risk Label(s) Packing None

group Environmental Not applicable.

hazards

Marine pollutant Yes

EmS Not available.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Packaging Exceptions Transport in bulk according to Annex II of MARPOL 73/78 and LTD QTY Not applicable.

the IBC Code

DOT



IATA; IMDG



Marine pollutant



### 15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication US federal regulations

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1) Listed. SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - No Hazard categories

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Pentane (CAS 109-66-0) Propane (CAS 74-98-6)

Safe Drinking Water Act

Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and

Chemical Code Number

Acetone (CAS 67-64-1) 6532

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Acetone (CAS 67-64-1) 35 %WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1) 6532

US state regulations

This product does not contain a chemical known to the State of California to cause cancer, birth

defects or other reproductive harm.

US. Massachusetts RTK - Substance List

Acetone (CAS 67-64-1) Butane (CAS 106-97-8) n-Heptane (CAS 142-82-5) Pentane (CAS 109-66-0) Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1) Butane (CAS 106-97-8) n-Heptane (CAS 142-82-5) Pentane (CAS 109-66-0) Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1) Butane (CAS 106-97-8) n-Heptane (CAS 142-82-5) Pentane (CAS 109-66-0) Propane (CAS 74-98-6) US. Rhode Island RTK

Acetone (CAS 67-64-1) Butane (CAS 106-97-8) Pentane (CAS 109-66-0) Propane (CAS 74-98-6)

### US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

#### International Inventories

**Philippines** 

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No

(PICCS)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Philippine Inventory of Chemicals and Chemical Substances

# 16. Other information, including date of preparation or last revision

08-14-2014 Issue date

Version #

The information in the sheet was written based on the best knowledge and experience currently Disclaimer

available. The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only

to the specific material designated and may not be valid for such material used in combination with

any other materials or in any process, unless specified in the text.

Product name: 13 OZ SW FAST TACK 382 MIST ADH LT 12PK Product #: 1000010130 Version #: 01 Issue date: 08-14-2014 No

Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).